Expended Ordnance Brass Casing Deformer Deformer



Model #18852

Patents: 5,558,281 & 5,772,134



BOULDINCORP **Demilitarization** Equipment

BouldinCorp Demilitarization Equipment P. O. Box 7116 McMinnville, TN 37111-7116

Toll Free: (800) 443-6398 Phone: (931) 815-8520 Fax: (931) 815-2741 www.bouldincorp.com E-mail: info@bouldincorp.com This machine is capable spent deforming cartridges, up to and including 20mm, beyond the point of reuse.

The deformer chamber contains M4 tool steel blocks hardened specific Rockwell Scale. These are attached to a high speed revolving drum grinder.


The patented hammers strike the brass casings as they pass through the deformer chamber, resulting in mechanical deformation meeting demilitarization requirements.

- Reduce Process Cost
- Decrease Process Time
- Effectively Demilitarize



GSA Contract: GS-07F-5703P

Mobile Expended Ordnance Deformer



8' x 24' Low Profile Trailer

Electric break-away safety system, marker lights, turn signals, & brake lights, unit is permanently mounted to dual axle trailer, dot approved for highway use



Large Hopper

Mounted hopper allows for easy loading with barrels or up to 5' bucket

Specifications:

Model # 18852

Engine 80 hp Cummins

Processing Rate 8,000 - 11,000 lbs./hr³

Controls Keyed Start, Emergency Shutoff

Grinder High Speed Rotary Drum

Fuel Diesel

• In-Feed Conveyor 14" x 12' vulcanized cleated belt

Discharge Conveyor 14" x 12' vulcanized cleated belt

Conveyor Motors
 Hydraulic Tank Drive

* Processing Rate is dependent on caliber of ordnance being processed, (up to 20 mm)




Rotary Grinder

High speed grinder deforms expended ordnance through hardened steel teeth

Stationary Expended Ordnance Deformer

Brass Casing Deformer also available as a Stationary Expended Ordnance Casing Deformer



Specifications:

(two models available)

Model # 18850 - 50 HP

Power 480v three phase

Processing Rate 8,000 -11,000 lbs./hr*

Conveyors 14" x 12"

Model # 18853 - 10 HP

Power 220v three phase

Processing Rate 1,000 -2,000 lbs./hr*

• Conveyors 6" x 12'

Processing Rate is dependent on caliber of ordnance being processed, (up to 20 mm)



Proudly Designed and Manufactured in America



BouldinCorp reserves the right to change product specifications without prior notice. © 2008, Bouldin Corporation All Rights Reserved.